



FE-1045 Technical Data



FE-INTERLININGS

FE-INTERLININGS

| | | | | | | |
|--|---|-------------------|-----------|-----------|-------|-------------------|
| 1. Specification | | | | | | |
| Supplier Article No. | FE-1045 | | | | | |
| Color(s) | WHITE - CHARCOAL | | | | | |
| Origin | CHINA | | | | | |
| Supplier Name | TELPA TEKSTIL URUNLERI DIS TIC.LTD.STI. | | | | | |
| Width (cm) | 90 CM | | | | | |
| Thickness (mm) | | | | | | |
| Roll length (rm/roll) | 200 / ROLL | | | | | |
| 2. Construction | | | | | | |
| Grey fabric | | | | | | |
| Composition (%) | POLIESTER | | | | | |
| Construction | NONWOVEN | | | | | |
| Weight (g/m ²) - (A) | FINISHED GOODS : 45 | | | | | |
| Yarn | | | | | | |
| Yarn Composition (%) | Warp | | Weft | | | |
| Yarn Density (thread/inch) | Warp | | Weft | | | |
| Woven Yarn Count (Denier) | Warp | | Weft | | | |
| Knit (gauge/inch) | Warp | | Weft | | | |
| Weft-inserted (gauge/inch) | Warp | | Weft | | | |
| Coating | | | | | | |
| Coating Method | DOUBLE DOT | | | | | |
| Composition (%) | | | 100% PA | | | |
| Dot Size (dot/cm ²) | | | | | | |
| Adhesive Weight (g/m ²) | Top Dot | 8~10gsm | Sub Dot | | | |
| Total Adhesive Weight (g/m ²) - (B) | | | | | | |
| Total Weight (g/m ²) (ISO9073-1) = (A + B) | | | | | | |
| 3. Oeko-tex 100 Standard | | | | | | |
| Class | | | Cert. No. | | | |
| Valid Until | | | | | | |
| 4. Formaldehyde | | | | | | |
| Japan Law 112 (ppm) | | | | | | |
| Other, please specific | | | | | | |
| 5. Fusing Conditions | | | | | | |
| Setting Temperature (°C) | | | | | | |
| Fuseline Temperature (°C) | 125~150 | | | | | |
| Time (second) | 10~15 | | | | | |
| Pressure | | N/cm ² | | Bar | 1~1,5 | Kg/m ² |
| 6. Care Labels | | | | | | |
| Washing (°C) | 40±3 | | Other | | | |
| Bleaching | | | | | | |
| Dry clean (P) - P=Perchloroethylene | AVAILABLE | | | | | |
| Prepared by : | TELPA TEKSTIL | | Date: | 1.08.2019 | | |